



荣冠陶瓦
RONGGUAN ROOFING TILE



FLAT TILE / ROMAN TILE / LUCA TILE / SPANISH TILE / BARREL TILE

平板瓦 / 罗曼瓦 / 卢卡瓦 / 西瓦 / 天筒瓦



目录索引

INDEXES



The artistic and intelligent design of
tile ridge of modern cultural architecture
当代文化建筑瓦脊的艺术设计智造

A 传统传承的辉煌

The brilliant traditional heritage

瓦的发展 _____ 02

The development of roofing tile _____ 02

中国古大瓦建筑 _____ 02

China's ancient roofing tile buildings

B 荣冠使命

Rongguan Mission

荣冠陶瓦发展简史 _____ 04

Brief history of Rongguan roofing tile

C 荣冠创新智造

Rongguan intelligent manufacture

企业介绍 _____ 07

Enterprise Profile _____ 07

五大优势 _____ 09

Five major advantages _____ 09

产品理念 _____ 09

Product ideas

D 荣冠建筑生态演绎

Rongguan architectural ecology interpretation

平板瓦 _____ 11

Flat tile _____ 11

罗曼瓦 _____ 29

Roman tile _____ 29

卢卡瓦 _____ 47

Lukartsa _____ 47

西瓦 _____ 56

Scandinavia tile _____ 56

天爵瓦 _____ 90

Tianjie tile _____ 90

E 花脊筒瓦系列


Flower ridge tile series _____ 107

公司荣誉 _____ 108

Company honor _____ 108

工程案例 _____ 109

Project case _____ 109



RONG GUAN

**The brilliant
traditional heritage**

传统传承的辉煌



RONG GUAN
Mission
荣冠使命

细数荣冠发展史的多个第一



Brief history
of Rongguan roofing tile
荣冠陶瓦发展简史

2007/10

第一条西瓦 S1 生产线

The first production line of spanish S1 tile

荣冠首条生产线破土动工建设，核心生产设备引进日本设备及技术。

Rongguan started the initialisation of the first production line of spanish tile. The core technique and machine is from Japan.

2008/10

荣冠第一件西瓦 S1 正式下线

The first Spanish roofing tile S1 was officially produced.

2011/10

第二条西瓦生产线建成正式投产

The second production line of Spanish roofing tile was officially put into use.



2011/11

第一条天筒瓦 T1 生产线正式投产

The first production line of Barrel tile T1 was officially put into production.

2011年11月10日，国内第一条天筒瓦全自动生产线正式投产，该自动化生产线由荣冠自主研发、设计、开发、填补了国内自动化生产天筒瓦的空白。

On 10th Nov 2011, The first fully automatic production line of Barrel tile in China was officially put into production, researched, designed and developed by Rongguan, which fill a vacancy in the field of fully automatic production line of Barrel tile in China.

2013/12

西瓦烧结隧道窑申请了实用新型专利，提高了西瓦的生产效率和产品质量。

The patent of utility models application for Spanish燒結 tunnel kiln which highly improves the production efficiency and quality, was gotten.

2014/07

西瓦干燥窑推进装置发明专利

Spanish dry kiln Patent on the invention of propulsive apparatus.

2014年7月7日西瓦干燥窑的干燥窑推进装置申请了发明专利，代表我司的干燥技术和速度有一个飞跃的提升，使产品发热均匀，减少缺陷面高了产品优等率。

On 7th July 2014, the patent on the invention of propulsive apparatus application for the truck of Spanish dry kiln, which means Rongguan's dry technique and speed were highly improved. It makes the product heated evenly and the excellence rate of product improved.



2014/11

平板瓦和罗马瓦专利申请

Patent applications for flat tiles and Roman tiles

2014年我司推出国内最大尺寸的平板瓦和罗马瓦，并就外观设计和实用申请了专利，提升了屋内建筑屋面的外观效果。

Rongguan launched the biggest Flat tile and Roman tile in China and applied for the patent of its design and practical use, which highly improved the look of the building.



**Brief history
of Rongguan roofing tile**
荣冠陶瓦发展简史

2015/05

第一件荣冠罗马瓦诞生

The first Rongguan Roman tile was borned.

公司引进欧洲核心设备及技术，生产的第一件罗马瓦正式下线，填补了国内大规模罗马瓦生产的空白。

Rongguan introduced European core machine and technique. The first Piece of Roman tile was officially produced, which filled a vacancy in the field of Roman tile in China.



2015/06

第一件荣冠平板瓦诞生

The first Rongguan Flat tile was borned.

公司引进欧洲核心设备及技术，生产的第一件平板瓦正式下线，填补了国内大规模平板瓦生产的空白。

Rongguan introduced European core machine and technique. The first Piece of Flat tile was officially produced, which filled a vacancy in the field of Flat tile in China.

2017/06

第一件荣冠卢卡瓦诞生

The first Rongguan Luka tile was borned.

公司引进欧洲核心设备及技术，生产的第一件卢卡瓦正式下线，填补了国内大规模卢卡瓦生产的空白。

Rongguan introduced European core machine and technique. The first Piece of Luka tile was officially produced, which filled a vacancy in the field of Luka tile in China.

2017/08

第一个省级企业工程技术中心

The first provincial level engineering technology center

公司是在同行业中唯一一家被省相关部门授予省级企业工程技术中心的企业。

Rongguan is the sole company in the same industry awarded to be the provincial level engineering technology center by Provincial government.

2017年桂河产品高耐候环保平板瓦 - 高强度节能罗美瓦 - 高强度低吸水率西班牙瓦，先后均被认定为广东省高新技术产品和佛山市创新项目产品。

In 2017, our products have been identified as high-tech products of Guangdong Province and innovative products of Foshan City. There are high weather-resistant and environmental friendly Flat tile, high-intensity energy-saving Roman Tile, and high-strength with low-water absorption rate Spanish Tile.



我们的步伐不断的前进，

We are going forward,

为市场带来更多更好的陶瓦产品……

Bring clay roofing tile to the market, better and more.

RONG GUAN
**Intelligent
manufacture**
荣冠创新智造



荣冠瓦大厂率先进行技术革新，采用微空心型支架承托瓦片的烧制，减轻支架本身的质量，从而减少能耗。同时该产品烧结后不会出现变形等产品缺陷，提高产品的质量。并创新地生产485mm*315mm 的罗马瓦和477mm*306mm 的平板瓦。两种规格均是同行业内规格最大，我们公司也是唯一能够生产该类型产品的企业。

Rongguan Clay tiles carry out technological innovation and successfully use of Hollow Hollowed bracket supporting tile firing, helping the weight of the bracket itself, thereby reducing energy consumption, while making the product not be deformed after sintering, or other defects, to improve product quality. And innovative production of 485mm * 315mm Roman tile and 477mm * 306mm flat tile. Both specifications are the largest in the industry specification, which is produced by our company who is also the only company that can produce this type of product.



荣冠陶瓦 / 企业简介

佛山市荣冠玻璃建材有限公司，始建于1986年，专注大型装饰建材三十载。是中国南方具有规模的大型装饰建材企业，主要生产石英石、岗石（又称工程石、合成石）、陶瓦。

本公司于2006年起，从国外原装进口多套生产设备，专业生产荣冠西班牙瓦、天简瓦、罗曼瓦、平板瓦、卢卡瓦，年产烧结瓦达5000多万件。优质的陶土、先进设备和生产工艺，保证每一片荣冠陶瓦均可以质量稳定、色均质优、尺寸一致，物理性能各项指标优于国家标准GB/T21149-2007标准，具备隔热、耐久，而且色彩艳丽等特点。

荣冠陶瓦，不只是避风挡雨单一功能的普通屋面瓦，更是传承了欧洲巴洛克风格和制作工艺的艺术品。每一片荣冠陶瓦都彰显着古典而华贵的欧洲宫廷气派，皇家贵族血统，都是淬炼出最出色的欧式古典瓦。古朴而富有内涵，华贵而极具气质，雅致而兼收韵味，尽显欧洲巴洛克之美，是各大中高档酒店别墅、楼宇亭台、大型商业中心等欧式建筑的不二之选。



Foshan Rongguan Glass Material For Building Co., Ltd., was founded in 1986, focusing on large decorative building materials for 30 years, which is a large scale decorative glass building materials enterprise in South China. We mainly produce Quartz stone, Artificial stone, known as Engineered stone, synthetic stone, Clay roof tile.

Since 2006, our company have imported many sets of production equipments from abroad, which specialize in producing Spanish tile, Espanol tile, Roman tile, Flat tile, and Luca tile, with the annual output more than 50 million pieces. High quality raw clay material, advanced equipments and production technology to ensure that Rongguan's Clay roof tile can be stable quality, uniform color and size, the physical performance of various indicators is better than the GB/T21149-2007 standard of national lighting tile, further with the characteristics of heat insulation, endurance, and bright-colored.

Rongguan clay roof tile is not just the roof tile to keep you away from the wind and rain, but also the art inherited European design and craft. Each piece represents the classical and elegant classic characteristic, it's the most outstanding European design roof tile. Simple while rich inside, generous and delicate, graceful and full of lingering charm, reflects Europe beauty, it's the ideal choice for all kinds of middle - high end hotel, villa, building, commercial centers in European design use.



“荣冠平板瓦”和“荣冠罗马瓦”的出品，填补了国内高端项目依赖进口瓦的一项空白。我们不断努力是为了让广大客户享受优惠的价格，享受最优质的进口瓦品质，让建筑楼盘更加绚烂辉煌。

荣冠陶瓦，传承欧洲4000年的传统生产工艺，从欧洲引进完整进口设备和生产技术，设立独立生产线，生产“荣冠平板瓦”和“荣冠罗马瓦”，年销量达到2000万件。国内首家采用源于欧洲的宽体隧道窑生产技术，加以顶烧的生产方式，使用欧洲一流的生产设备作为生产的核心设备，确保每一片“荣冠平板瓦”和“荣冠罗马瓦”都是荣冠高品质出品。与此同时，荣冠陶瓦秉承传统生产工艺，使用传统石膏成型模具，有效地保证了瓦面的光滑平整，同时极大地丰富了瓦的菱角、线条和造型，力求尽显欧洲古典美的魅力所在。

The production of Rongguan flat roof tile and roman roof tile meet market demands successfully. It changes the situation that high end projects rely on import roof tiles. We make efforts to offer wide customers the most favorable price, let them experience premium quality same as import, to make the construction buildings more brilliant.

Rongguan inherit European four thousand years traditional crafts, import production lines and facilities from Europe, manufacture flat roof tile and roman roof tile, annual production capacity reaches 20 million pieces. We are the first enterprise in China who adopt wide tunnel kiln which origin from Europe. Combined with top firing method, to make every piece clay roof tile have premium quality. Meanwhile, Rongguan use traditional plaster mould, this makes roof tile surface looks smooth and flatness, its edge, line and style is more clean out, express European roof tile charms in a better way.



“荣冠平板瓦”、“荣冠罗马瓦”秉承欧洲瓦古典而华贵之余，更加增添地中海的古朴深邃和时尚雅致。简单的线条，饱满的流线型弧度，丰富的色彩既可以为传统的建筑增添古典的味，也可以为现代的建筑带来时尚的风潮。

Rongguan flat roof tile and roman roof tile inherit the classic and magnificence of European roof tile, with the addition of Mediterranean simple and fashion beauty. Brief lines, smooth surface, variety colors, Rongguan clay roof tiles make traditional construction classical, modern construction fashionable.



Five major advantages 五大优势



尺寸一致
The coincident size

荣冠陶瓦严格按照国家烧结瓦 GB/T21149-2007 标准进行生产，尺寸标准，并且不变形，单个瓦件和不同批次之间的尺寸允许偏差均符合国际的要求。



品种齐全，色泽丰富
Various range

荣冠陶瓦风格品种齐全，有质朴无光、古朴亚光、亮面釉面等多种风格的主瓦和各种配件。并且颜色丰富，色泽均匀，各种色讲古朴自然，立体感强，也可以按图客户要求。所要颜色制造加工，使用者或设计师可根据自己个性及风格选择花色品种，演绎独特的装饰效果。



外观质量稳定
The appearance of stable quality

荣冠陶瓦产品质量良好，烧结温度控制精确，无欠火、分层缺陷等外观不良现象。



化学性能稳定
Chemical stability

荣冠陶瓦的制造工艺国际领先的水平，使其产品具有了稳定性，可靠的质量保证。相比烧结粘土瓦和水泥瓦，荣冠陶瓦具有色彩稳定性耐久，抗化学腐蚀（酸雨）能力以及耐候性（如抗紫外线）好等特点。



物理性能良好
Good Physical properties

荣冠陶瓦吸水率低，抗折强度高，抗弯曲强度高，其弯曲破坏度大于1600N，抗冻性较好，经-50℃次冻融循环不出现脱落、掉角、掉棱以及裂纹增加的现象，耐急冷急热性好，粘土类瓦经10次急冷急热循环不出现炸裂、剥落以及裂纹延长现象，吸水率小，吸热好等。



荣冠陶瓦，对产品研发过程近乎达到了过分要求，我们只向客户提供最完美的款式设计与最好的品质。我们拥有全行业最强大的核心技术团队，重金购进大吨位陶机生产线作为品质保证的后盾，健全的产品线满足不同的品位需求，优质的产品口碑，无可匹敌的销售网络，首屈一指的客服服务、产品品质和研发设计，是现代人追求奢华品位的首选。

Rongguan Clay tiles, with the process of product development almost reached a high demand, are provided to customers with the most perfect style design and the best quality. We have the most powerful core technology team. In this industry, paid a high price to large tonnage production line as the backup of quality assurance. The most complete product line can give the products to meet the needs of different tastes, help us to earn the reputation of high-quality products. The invincible sales network, first-class customer service, product quality and design from R&D, make it to be the first choice of modern and luxury decoration.



=设计 Design



=生产 Production



=质检 Quality Inspection



=出货 Shipping

RONG GUAN

**Architectural ecology
interpretation**

荣冠建筑生态演绎

FLAT TILE

平板瓦

Size: 470x100mm

ROMAN TILE

罗曼瓦

Size: 495x319mm

LUKA TILE

卢卡瓦

Size: 460x295mm

SPANISH TILE

西瓦

Size: 310x315mm

BARREL TILE

天筒瓦

Size: 365x175mm



RONG GUAN

FLAT TILE 平板瓦 series

彷如海风拂过般舒适 /

禅学与美学的完美结合

简洁时尚的线条，别具一格的生活态度。
享受五彩缤纷生活的同时，坐拥宁静的港湾，
外面的世界很精彩，家的臂弯很宽广。
就让我们一同感受这美好的一切。

So comfortable as the sea wind breezing/
the perfect combination of Zen and Aesthetics.
Tense and fashion lines,
a unique attitude towards life.
Enjoy colorful life and...
sit in the peaceful harbour.
Wonderful outside, cozy home.
Let's feel all the good things.



Behind the scene of space art comes the immortal aesthetic legend of value.

极致空间艺术的背后，源自价值不朽的美学传奇。
www.rongguanco.com



保利西上



最原始的平瓦设计，风
雨很难渗透，雨水能快速、最
直接地排出，是极具实用性的屋面瓦。
现代生产工艺和屋面瓦防漏系
统下，更加为平瓦瓦带来良好的
隔热性能。作为屋面装饰，平
瓦瓦为现代建筑带来更多的古朴
韵味，如穿墙时代的老人，沧桑
而深邃。

The most original flat tile design,
which the wind and rain is difficult to
penetrate, rain can quickly and smoothly
discharge, is the most practical roof
tile. Modern production technology and
roof tile leak-proof system can give the
flat roof tiles better thermal insulation
properties.



工程项目：保利·琥珀四季城 使用产品：WZSF1灰瓦



荣冠平板瓦，使用传统瓦型模具，有效地
保证了瓦瓦的光滑平整，极大地丰富了瓦的
线条和造型，力求尽现欧洲巴洛克瓦的魅力所在。
“荣冠平板瓦”，采用优质陶土，先进进口设备
和经典工艺配方，经过1100度高温一次烧制而成。
釉面持久不脱落，具备不起皮、不掉屑、不反霜
的特点。简单的线条，勾勒流畅的平面，加上神
妙繁多的颜色，让“荣冠平板瓦”很好地融合了当
代建筑和古典建筑的特点，使画面更是大气，颜色
亮丽。线条整齐划一，展现独特的韵味，更能
彰显建筑的历史韵味。

Rongguan flat tile use traditional plaster mold, effectively
ensure the smooth and smooth tile surface, it greatly enriched
the tile's edges, corners, lines and shapes. We try our best
to make the most of the charm of classical European tiles.
Rongguan flat tile are made from high-quality clay, advanced
imported equipment and excellent technology formula. Burned
under 1100 degree high temperature, the glazed surface does
not fall off, and keep the resistance to wind, angel broken
and whitening.



工程项目：江西·宜春天佑花城

使用产品：W57#1 隔断



平板瓦特点

平直的瓦面设计决定了平板瓦具有极高的实用性。瓦面的平直度，不仅使其具有其他屋面瓦难以匹配的排水性能，更使得瓦面不容易积累风雨带来的杂物，尤其对东北、内蒙古地区雪量比较大的建筑更有利排水。减少形成冰坝对人身安全及车辆的损伤。装饰效果上，平板瓦为建筑带来自然古朴的韵味。制作的奢华，回归自然。现代先进的生产工艺，平板瓦经过高温烧结压制，使其具有良好的抗压性。色彩与质感更丰富，更加适应现代建筑的要求。



The feature of Flat Tile

Flat tile design determines it has a very high practicability. The smoothness of the tile surface not only makes it match the drainage performance that other roof tile is difficult to do, but also makes it difficult for the tile surface to accumulate the debris brought by the wind and rain. Especially for the northeast, Inner Mongolia snow relatively large building more conducive to snow, reduce the formation of ice damage on personal safety and vehicle damage. Modern advanced production technology, flat tile after burning at high temperature, it's anti-pressure, colorful and more different shapes, better to adapt to the requirements of modern architecture.

平面瓦参数

The parameter of Flat Tile

外形尺寸 External dimensions	477mm x 305mm
有效摆渡尺寸 Effective lap size	385mm x 265mm
重量 Weight	约 4.4kg/ 片 About 4.4kg/pcs
单位用瓦量 Pcs/m²	约 9.8 片 / m² About 9.8pcs / m²
吸水率 Water Absorption	< 6.0% (I类瓦) < 6.0% (Class I瓦)
抗弯曲性能 Bending resistance	> 1200N
耐急冷急热性 Resistant to cold&hot	经 10 次急冷急热循环不出现炸裂、剥落及裂纹延伸现象 After 10 times the rapid heating & cooling cycle there is no appearance of bursting, spalling or cracking extension
抗冻性能 Frost resistance	-55~40℃，50 次循环不出现剥落、掉角、掉棱及钢丝增加现象 At -40 ℃ , 50 times cycle without spalling, corner defect, wire augment
防火指标 Fire safety index	完全不燃 Completely non-flammable
最小安装坡度 Minimum installation slope	16.7° (由于防倒流方面的考虑, 建议安装坡度大于 16.7°) 16.7° (Due to the consideration of anti-reflux, it is recommended to install the slope bigger than 16.7°)
最大安装坡度 Maximum installation slope	90°
搭接尺寸 Lap size	上下搭接 92mm, 左右搭接 40mm Up&Down lap 92mm, Left&Right lap 40mm
排水条间距 Quantity of batten/rain-water lath	约 1.68m/ m² (间距 600mm) About 1.68m/ m² (Distance 600mm)
排瓦条间距 Quantity of tile batten	2.6m/ m² (间距 385mm) 2.6m/ m² (Distance 385mm)
固定瓦片用钉量 Tile fixed with nail/sqm	约 20 颗 About 20/sqm

FLAT TILE 平板瓦

Sizes: 477X305mm



W058-F1 星空黑



W57-F1 深黑



W51-1-F1 棕咖啡



W51-2-F1 中咖啡



W51-3-F1 深咖啡



W25-F1 苏啡

RONG GUAN容冠



工程项目: 唐州·牧云溪谷
使用产品: W058-F1 星空黑

图片仅供参考, 使用时请以实物为准。 For reference only, please refer to the physical product.

FLAT TILE 平板瓦

Sizes: 477X303mm



W55-F1 相红



W84-F1 红曲



W85-F1 天山红



W80-2-F1 白红



M217-F1 沙影



C109-F1 云影

RONG GUAN容冠瓦



工程概况：佛山 - 保利云上

使用产品：W058-F1 星空黑 10%、W026-F1 墨灰 30%、W61-F1 雾烟 60%

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

FLAT TILE 平板瓦

Sizes: 477X203mm



W32-F1 深蓝



W61-F1 深褐色



Y62-F1 雅白



Y70-F1 白夜黑



W30-F1 深蓝



W028-F1 星空灰



工程案例：苏州·建发独墅湾
使用产品：W028-F1 星空灰

图片仅供参考，实际请以实物为准。 For reference only please refer to the physical product.

Project case of Flat tile
平板瓦工程案例

RONG GUAN 容冠



Y666-F1 香槟金



Y668-F1 深卡其



工程项目：武汉·美联美林匹克学校
使用产品：WS7-F1 深黑

图片仅供参考，如需订购请以实物为准。 For reference only, please refer to the physical product.



工程项目：北京·城建领悦居
使用产品：W062-F1 无光植筋黑

图示仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.



工程项目：北京·首城汇景墅
使用产品：W57-F1 无光深黑

图片仅供参考，欲知相关产品参数，请参阅产品说明书。For reference only, please refer to the product manual.

Project case of Flat tile
平板瓦工程案例

RONG GUAN PARK



工程项目：海南·博鳌机场

使用产品：W51-2-F1 中海硅

图片仅供参考，使用请以实物为准。 For reference only, please refer to the physical product.

Project case of Flat tile
平板瓦工程案例

RONG GUAN 宏润瓦



工程项目：海口·美安热府
使用产品：W55-F1 品红

图片仅供参考，需到现场看实物为准。 For reference only, please refer to the physical product.

Project case of Flat tile
平板瓦工程案例

RONG GUAN®RUI



工程项目：长沙 - 龙脉台
使用产品：W30-F1 高蓝

图示仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Project case of Flat tile
平板瓦工程案例

RONG GUAN荣冠瓦



工程案例：北京·紫悦花园
使用产品：W51/2-F1 中咖啡

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Flat tile - Accessory introduction
平板瓦 - 配件介绍

RONG GUAN 美耐瓦



Sizes: 395X395mm
F4 西瓦



Sizes: 347X285mm
F5 单瓦



Sizes: 400X255mm
F7 半脊收口



Sizes: 345X210mm
F7A 平板瓦收口



Sizes: 390X425mm
F9 三瓦



Sizes: 220X230mm
F10 正脊收口



Sizes: 345X285mm
F11 正脊收口过渡



Sizes: 477X120mm
FB3 半边左挂瓦



Sizes: 477X120mm
FB4 半边右挂瓦



Sizes: 477X175mm
FB1 半边主瓦




Sizes: 350X255mm
R2 水沟瓦


此图仅供参考，使用时请以实物为准。 For reference only please refer to the physical product.

Product Usage Information
产品用量信息表

RONG GUAN 瓦通瓦



平板瓦 F1/FB3/FB4 搭接示意图 (人字坡屋面)
Flat tile F1 / FB3 / FB4 installation diagram ("A" Slope roof)




F5/F10/F11 搭接示意图
F5/F10/F11 installation diagram

名称 Name	单方用量 Usage quantity	重量 (kg) Weight (kg)	尺寸 (mm) Size(mm)	备注 Remark
F1	约 9.8 片 / m about 9.8pc/m	4.6±0.2kg	477*305	有效尺寸 385*265mm Effective size 385*265
F4 叉	1 片 / 点 1pc/spot	4.5±0.2kg	395*395	
F5	3.5 片 / m 3.5pc/m	2.95±0.2kg	347*285	有效长度约 310mm Effective length 310mm
F7	1 片 / 点 1pc/spot	3.2±0.2kg	400*255	
F7A	1 片 / 点 1pc/spot	2.5	345*210	
F9	1 片 / 点 1pc/spot	3.8±0.2kg	390*425	
F10	1 片 / 点 1pc/spot	1.38±0.2kg	220*230	用于人字坡正脊收口 For "A" shape ridge ending
F11	1 片 / 点 1pc/spot	2.9±0.2kg	345*285	人字板屋面使用。与 F5、F10 搭接使用 Connect with F5,F10 for "A" shape slope
FB3	2.5 片 / m 2.5pc/m	3.3±0.2kg	477*120	左收边瓦，与 F1 直接搭接，有效长度与 F1 相同 Left side ending tile for slope
FB4	2.5 片 / m 2.5pc/m	3.4±0.2kg	477*120	右收边瓦，与 F1 直接搭接，有效长度与 F1 相同 Right side ending tile for slope
FB1	2.5 片 / m 2.5pc/m	2.8±0.2kg	477*175	工字贴使用，与 F1 (或 FB3/FB4) 直接搭接，有效长度与 F1 相同 For "H" shape installation, length is the same as F1(main tile)
R2	3.5 片 / m 3.5pc/m	2.3±0.2kg	350*255	有效长度约 300mm Effective size 300mm

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Accessories Usage Diagram
配件使用示意图

RONG GUAN 容观




图示仅供参考，使用时请以实物为准。 For reference only please refer to the physical product.

与一般的方案相比，使用这套解决方案可以获得以下额外价值

Compared with the general program, the following additional value can be obtained by using this solution:


- 屋面结构优化，节约成本与工时
Roof structure optimized, cost and working hours saved.
- 良好防水能力提供额外的屋面保护
Good waterproofing which provides additional roof protection.
- 结构中的空气层可以增强保温功能，或减少保温板厚度
The air layer in the structure can enhance the insulation function, or reduce the thickness of the insulation board.



木制顺水条必须垂直 (90°) 于木底瓦条。

木条间距请参考上图。(跳出檐口 80~60mm)

The bottom of non-water bath must be vertical (90°). On bottom of tile.
Space between batten please refer to above figure. (Extend out of eave 80~60mm)



主瓦安装次序：从右下角开始向左向上安装。

主瓦间距请参考上图。

The space between main tiles please refer to above figure.

ROMAN TILE

罗曼瓦 series

温馨浪漫的艺术生活 / 罗曼蒂克的享受

这里安详、自然、美丽和纯净，仿佛时光倒流一切都变得缓慢懒惰。
这样的生活既美好又让人不知所措。
每天只静静的站在阁楼的阳台上，
看夕阳西下，一切都那么美丽和宁静。

*Cozy and romantic life of arts/romantic enjoyment
Peace,natural,beautiful, and pure light here.
Everything goes so slowly as if it is back in time
Such a good life,
to make people unprepared to do anything.
But just stand on the veranda of garret,
and enjoy sunset in beauty and silence.*

RONG GUAN

Behind the scene of space art comes the immortal aesthetic legend of value.

极致空间艺术的背面，蕴藏价值不朽的美学传奇。
www.rongguan.com



深冠罗曼瓦 485mm x 315mm 同行规格最大，铺瓦方式简洁、高效、省工、省料，且有效面积大，有重量更重和用量减少为传统屋项的三分之一。

荣冠罗曼瓦在秉承欧洲古建筑华贵之余，根据中国实际情况加以改善，比起现有的欧洲瓦，强度更大，更适合国内气候条件，防水能力更强。

Rongguan Roman roof tile 485x315mm is the biggest size among peers, its installation is simple, effective and time cost. Due to its large effective area, the roof weight and use quantity can be cut to one third of the traditional roof tile.

Rongguan roman roof tile inherit the classical and gorgeous characteristic of European roof tile, improved upon Chinese situation, more curved and suitable to be used under China weather condition than Europe roof tile.

“深冠罗曼瓦”使用天然质朴的传统陶土材料，经过1100度的高温烧制，拥有绝密耐热性、极好的抗冲击强度、卓越的隔热隔声性能。“深冠罗曼瓦”融入现代科技和美学理念，赋予产品现代美学和高品质的特点，既保持传统风格，又融入时尚设计。

Rongguan roman roof tile is made from natural raw material of clay, burned in temperature of 1100 °C, have good performance in anti freeze, shock resistance as well as heat and sound insulation.



有别于平直瓦的简单直线，有别于西班牙瓦的单纯曲线，罗马瓦更像两者结合体，直线与曲线相融合，实用性与装饰性的完美产物。同样的直线平板设计，使得罗曼瓦具有良好的排水防水功能，由曲线交织而成的拱形，为整体罗曼瓦增添不一格的典雅的艺术气息。

Different from the straight flat roof tile or curved spanish roof tile, roman roof tile is just like the combination of these two. Straight mix with curve, it is practical and decorative. Straight design let roman roof tile drain quickly, curve shape make the installation easy.

工程场景：豪门易经·卢卡小镇
使用产品：KODA 单玻·C03双三玻



图示仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.



罗曼瓦特点

容易铺设，有许多配件供选择。因此能很好地适应任何一种建筑风格，无论是现代或者是传统。最大尺寸规格，节省瓦片使用量，降低施工材料的重量及人工费用。为客户提供最具经济效益的选择。同时，采用深锁扣的设计，可以在风浪易于安放的同时，保证铺设瓦件层面的安全。



The feature of Roman Tile

There are a series of accessories to supply, tiles Mongguan roman tile can match the construction very well, no matter in modern or traditional style. Meanwhile its interlock design can guarantee the roof safety during and after installation.

罗曼瓦参数

The parameter of Roman Tile

外形尺寸 External dimensions	485mm×315mm
有效搭接尺寸 Effective lap size	405mm×265mm
重量 Weight	约 4.5kg/片 About 4.5kg/pcs
单位面积重量 Pcs/asm	约 9.3 片 / m ² About 9.3pcs / m ²
吸水率 Water Absorption	< 6.0% (1类瓦) < 6.0% (Class I tile)
抗弯曲性能 Bending resistance	≥ 160N
耐急冷急热性 Resistant to cold&heat	经 10 次急冷急热循环不出现炸裂、脱落及裂纹等现象 After 10 times the rapid heating & cooling cycle there is no appearance of bursting, peeling or cracking extension
抗冻性能 Frost resistance	经 -40℃，50 次循环不出现剥落、掉角、掉棱及裂纹增加现象 At -40 ℃ , 50 times cycle without peeling, corner defect, or cracking augment
防火指标 Fire safety index	完全不燃 Completely non-flammable
最小安装坡度 Minimum installation slope	16.7° (由于防倒流方面的考虑，建议安装坡度大于 16.7°) 16.7° (Due to the consideration of anti-reflux, it is recommended to install the slope bigger than 16.7°)
最大安装坡度 Maximum installation slope	90°
搭接尺寸 Lap size	上下搭接 80mm, 左右搭接 50mm Up&Down lap 80mm, Left&Right lap 50mm
耗水条用量 Quantity of batten/water strip	约 1.68m / m (间距 60mm) About 1.68m / m (Distance 60mm)
挂瓦条用量 Quantity of tie batten	2.5m / m ² (间距 405mm) 2.5m / m ² (Distance 405mm)
固定瓦片用钉量 Tile fixed with nail/ham	约 10 枚 About 10/nail

图片仅供参考，实物请以实物为准。 For reference only, please refer to the physical product.

ROMAN TILE 罗曼瓦

Sizes: 485x315mm

RONG GUAN 美丽屋



C201-R1 云彩



M217-R1 云彩



图片仅供参考，实际请以实物为准。 For reference only, please refer to the physical product.

ROMAN TILE 罗曼瓦

Sizes: 495X315mm

RONG GUAN 容冠



M104-R1 深棕



C201-R1 棕褐



W56-2-R1 吉普



W55-R1 单红



W85-R1 朱砂红



W80-2-R1 吉汇



W082-R1 吉汇



W85-4-R1 吉汇

图片仅供参考，选择时请以实物为准。 For reference only, please refer to the physical product.

ROMAN TILE 罗曼瓦

Size: 485x315mm

RONG GUAN 宏润瓦



Y96-R1 霁光顶红



L90-R1 欢颜红



A006-R1 单彩



W51-1-R1 深墨田



W22-3-R1 土黑



W063-R1 漆蓝



Y42-R1 兔耳蓝



Y62-R1 黑田

图示仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.



工程项目：桂林·博罗镇那花开酒店
使用产品：W57 深灰

图片仅做参考，最终请以实物为准。 For reference only, please refer to the physical product.

ROMAN TILE 罗蔓瓦

Size: 485X315mm

RONG GUAN 羽冠瓦



W57-R1 深灰



Y666-R1 咖啡色



W082-R1 赤红 90%
W51-1-R1 深咖啡 10%



W05B-R1 黑空黑



Y666-R1 咖啡色



Y62-R1 黑白 70%
W57-R1 深黑 30%

图示仅供参考，使用时请以实物为准。 For reference only please refer to the physical product.

Project case of Roman tile
罗曼瓦工程案例

RONG GUAN 罗曼瓦



工程项目：苏州·胡跋山庄
使用产品：W063-R1 紫蓝

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.



工程项目：海口·椰帆海岸
使用产品：W56-2 奶黄 10% W51-1 深咖啡 10% W55 海红 80%



图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Project case of Roman tile
罗曼瓦工程案例

RONG GUAN 罗冠瓦



工程项目：海口·长弘御墅
使用产品：A006-单彩 W082 赤红各 50%

图片仅做参考，最终请以实物为准。 For reference only, please refer to the physical product.

Project case of Roman tile
罗曼瓦工程案例

RONG GUAN 罗曼瓦



工程项目：北京·通州养老院
使用产品：W082-R1 无光赤红

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Project case of Roman tile
罗曼瓦工程案例

RONG GUAN 罗曼瓦



工程案名：厦门禹洲·卢卡小镇
使用产品：AD06 单彩 C5357 云彩

图片仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Roman tile - Accessory introduction
罗曼瓦 - 配件介绍

RONG GUAN 罗曼瓦



Sizes: 350X255mm
R2 水沟瓦



Sizes: 415X415mm
R4 四叉



Sizes: 350X280mm
R5 峰瓦



Sizes: 485X190mm
R6 左收边过渡瓦



Sizes: 390X260mm
R7 斜脊收口



Sizes: 420X450mm
R9 三叉



Sizes: 285X230mm
R10 正脊封头



Sizes: 485X175mm
R15 右檐口瓦




Sizes: 485X175mm
R16 左檐口瓦



Sizes: 345X280mm
R11 正脊收口过渡瓦



Sizes: 235X122mm
R 正直




Sizes: 310X220
G2 水沟瓦


图示仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.

Product Usage Information
产品用量信息表

RONG GUAN 容冠瓦



罗马瓦 R1/R6/R15/R16 搭接示意图（人字坡屋面）
Roman tile R1/R6/R15/R16 installation diagram (A shape sloping roof)



R5/R10/R11 搭接示意图
R5 / R10 / R11 installation diagram




前瓦格接示意图
Front shield installation diagram

名称 Name	单方用量 Usage quantity	重量 (kg) Weight (kg)	尺寸 Size(mm)	备注 Remark
R1	约 9.3 片 / m ² About 9.3pc/m ²	4.6±0.2kg	485*315	有效尺寸 405*265mm Effective size:405*265
R2	3.5 片 / m 3.5pc/m	2.3±0.2kg	350*255	有效长度约 300mm Effective length:300mm
G2	4 片 / m 4pc/m	2.3±0.1kg	310*220	有效长度约 250mm Effective length:250mm
R4 叉	1 片 / 点 1pc/spot	6.1±0.3kg	415*415	
R5	3.5 片 / m 3.5pc/m	3.0±0.2kg	350*280	有效长度约 310mm Effective length:310mm
R6	2.5 片 / m 2.5pc/m	3.0±0.2kg	485*190	左收边瓦 R16 与 R1 搭接过渡瓦，有效长度与 R1 相同 Left side ending tile, effective length is the same as R1
R7	1 片 / 点 1pc/spot	3.2±0.2kg	390*260	
R9	1 片 / 点 1pc/spot	5.0±0.3kg	420*450	
R10	1 片 / 点 1pc/spot	2.2±0.2kg	295*230	用于人字坡正脊收口 For "A" shape ridge ending
R11	1 片 / 点 1pc/spot	3.0±0.2kg	345*280	
R15	2.5 片 / m 2.5pc/m	3.5±0.2kg	485*175	右收边瓦，与 R1 直接搭接，有效长度与 R1 相同 Right side ending tile for slope
R16	2.5 片 / m 2.5pc/m	3.5±0.2kg	485*175	左收边瓦，与 R6 配搭使用，有效长度与 R1 相同 Left side ending tile for slope
R 正脊	8 片 / m 8pc/m	0.93±0.1kg	235*122	正脊两边收口使用，脊瓦安装后，真瓦见光的 140mm For ridge two side usage, visible size is 140mm after installation

图片仅供参考，需用实物看实物方法。 For reference only, please refer to the physical product.

Accessories Usage Diagram
配件使用示意图

RONG GUAN 红冠



图仅供参考，使用时请以实物为准。 For reference only, please refer to the physical product.


与一般的方案相比，使用这套解决方案可以获得以下额外价值

Compared with the general program, the following additional value can be obtained by using this solution:

- 屋面结构优化，节约成本与工时
Roof structure optimized, cost and working hours saved.
- 良好的防水能力提供额外的屋面保护
Good waterproofing which provides additional roof protection.
- 结构中的空气层可以增强保温功能、或减少保温板厚度
The air layer in the structure can enhance the insulation function, or reduce the thickness of the insulation board.




图片仅供参考，实际请以实物为准。 For reference only, please refer to the physical product.



木制滴水条必须垂直 (90°) 于木质瓦条。
木条间距请参考上图。(伸出墙面 80~60mm)

The batten of rain-water lash must be vertical (90°) on batten of tile.
Space between batten please refer to above figure. (Extend out of wall 80~60mm)



主瓦安装次序：从右下角开始向上向左安装。
主瓦间距请参考上图。

The space between main tiles please refer to above figure.

COMPANY HONOR
公司荣誉

RONG GUAN 容冠





部分工程名录: LIST OF PROJECTS USE OUR PRODUCTS



佛山市荣冠玻璃建材有限公司

FOSHAN RONGGUAN GLASS MATERIAL FOR BUILDING CO., LTD.

地址: 佛山市三水区白坭镇三水大道南161号

电话: +86-757-87562498, 87579806

传真: +86-757-87510282

Add :No.161, South Of Sanshui Avenue, Baiji Town, Sanshui District,
Foshan City, Guangdong Province

Tel : +86-757-87562498, 87579806

Fax : +86-757-87510282

E-mail: manager@rongguanco.com

www.rongguanco.com



微信公众号二维码



荣冠网址 APP 二维码
(仅适用于 iOS)

2018

2018年8月第2版

